

1U Rackmount 17" TFT LCD KVM switch (Short Depth), IP65

Model: KVM-1701COMBO-S-IP
1 port KVM Switch

Model: KVM-1708COMBO-S-IP
8 port KVM Switch

Model: KVM-1716COMBO-S-IP
16 port KVM Switch



Main Feature

- IP65 front protection for LCD screen
- IP68 - 106 keys Silicon keyboard with touch pad
- Short depth (460mm) 19" 1U Rackmount Design
- 1 x USB / PS2 console controls 1/8/16 directly connected computers
- Support DOS, Windows, Netware, Unix, Linux, Mac OS
- Hot Pluggable - Add or remove connected PCs without having to power down the KVM switch/PCs
- No software required - easy PC selection via Push Buttons, Hot Keys or OSD (on screen display)

Specification				
Product Model		KVM-1701COMBO-S-IP	KVM-1708COMBO-S-IP	KVM-1716COMBO-S-IP
LCD	Size	17" TFT		
	Resolution	1280 x 1024 DDC2B		
	Backlight	LED		
	Luminance	250 cd/m2		
	View Angle	176° (H) , 170° (V)		
	Maximum Color	16.7M		
	Contrast Ratio	1000 : 1		
LEDs / Port		1	8	16
Power LED		1		
Computer Connections		1	8	16
Maximum Computer Connections		225	232	240
Computer Connectors		1 x DB -15 female	8 x DB -15 female	16 x DB -15 female
Daisy Chaining		Daisy Chainable up to 8 levels; Connector: DB-15 (female type)		
Computer Selection		On Screen Display (OSD) , Hot Key , Push Button		

Hotkey		Provide various Hotkey (Scroll-Lock/ Cap-Lock / Num-Lock / Alt-Ctrl-Win)
Auto-Scan Intervals		5 ~ 99 Sec.
Keyboard / mouse Emulation		PS/2
Power Adapter		AC 100-240V , 50/60Hz , DC 12V / 4A , 48Watt
Housing		Metal
Size		19" Rack mount, 1U
Environment	Operating Temperature	0-50 °C
	Store Temperature	-20-60 °C
	Humidity	10% to 95%, non-condensing
Physical Dimensions (W x H x D)		448 x 45 x 485 mm
Packing Dimensions (W x H x D)		590 x 170 x 720 mm
Certificated		CE/FCC
Ordering Information		
KVM-1701COMBO-S-IP (1U Rackmount 17" TFT LCD ,with 1 port KVM switch (Short Depth), IP65)		
KVM-1708COMBO-S-IP (1U Rackmount 17" TFT LCD ,with 8 port KVM switch (Short Depth), IP65)		
KVM-1716COMBO-S-IP (1U Rackmount 17" TFT LCD ,with 16 port KVM switch (Short Depth), IP65)		
KCVU-018 (USB, 2 in 1 KVM Cable , 1.8 meter length)		KCVP-018 (PS/2, 3 in 1 KVM Cable , 1.8 meter length)
KCVU-030 (USB, 2 in 1 KVM Cable , 3.0 meter length)		KCVP-030 (PS/2, 3 in 1 KVM Cable , 3.0 meter length)
KCVU-050 (USB, 2 in 1 KVM Cable , 5.0 meter length)		KCVP-050 (PS/2, 3 in 1 KVM Cable , 5.0 meter length)

Structure Diagram

Unit :mm

